DVI CAT5 Extender Series

ITEM NO.: DE02E DVI CAT5 Extra Long Rang Extender over Single CAT5 Cable 100 Meters



DE02E DVI Extra Long Range CAT5 Extender is using only one cost effective CAT5E/6 cable to extend your HDTV display up to 100 meters at 1920x1200. With high quality uncompressed video to delivers significant value to the entire home and commercial entertainment system.

DE02E DVI CAT5 Extra Long Range Extender over Single CAT5 cable Features:

- Extends DVI Signal over one CAT5/5e/6 cable.
- Uncompressed high definition video up to 1920x1200@60Hz and 3D capable.
- Max. Data Rate- 10.2Gbps.
- HDMI 1.3 and HDCP compliance.
- Transmission range up to 100 meters at 1920x1200 resolution.


Installation view:




Cable:

Link cable recommend use high quality Cat.5e $\$ Cat.6 $\$ Cat.6a $\$ Cat.7 UTP / STP or FTP cable.

Panel view: DE02ET



DE02ER



Transmission Distance:

The maximum transmission distance up to 100meters, use lower resolution won't extend longer distance.

If connection through the wall socket, the cable length must less 5 meters between HDMI extender and wall jack, as below drawing:



RJ45 Define:

Video Link (TIA/EIA-568-B)

	/
1. Orange-white	DATA0 +
2. Orange	DATAO -
3. Green-white	DATA1 +
4. Blue	DATA2 +
5. Blue-white	DATA2 -
6. Green	DATA1 -
7. Brown-white	DATA3 +
8. Brown	DATA3 -

Caution:

- 1. The wiring must away from any equipment with electromagnetic wave, i.e.: mobile phone, microwave, radio equipment, fluorescent lamp, high voltage power lines.
- 2. This device is not network equipment, do not connect with Network to avoid damage.
- 3. IR transmitter do not put near from receiver to avoid mutual interference.

Package Include:

Transmitter x 1 piece Receiver x 1 piece Power adapter x 2 pieces

Specification:

ITEM		DE02ET	DE02ER	
Resolution		Up to 1920x1200 / 60Hz		
Distance		100M (Max)		
Connector		DVI-I (Digital Only)		
Power Supply		DC5V 2A Regulated		
Power Consumption		600mA (Max)	1200mA (Max)	
Temperature Operation: -40 to $+55^{\circ}$ C, Sto		Operation: -40 to $+55^{\circ}$ C, Storage	age: -40 TO 85 $^\circ\!\!\mathbb{C}$, Humidity: up to	
		95%		
Dimensions	mm	49.2 x 92 x 25		
Weight	g	130	140	
		130	140	

Rohs (EFCC

Rev. B