


N-Series Superior Night Vision 2 Megapixel Fixed Dome Network Camera

FD-202Np V5

HDTV 1080p/720p • 2M/1.3M Resolution Supported




- N-Series Sony Exmor 2-Megapixel Fixed Dome Camera
- **FocusEasy™** to Ease the Focus Adjustment via the Buzzer for notification
- HDTV Video Quality (Full HD 1080p @ 30fps)
- **Brickcom WDR Enhancement®** Technology
- H.264, MPEG-4, and MJPEG Triple-Codec Compression
- **Intelligent Multi-Profile Sensor Management®** for Different Environments
- Removable IR-Cut Filter & Auto Light Sensor for Day and Night
- 1 DI/DO for External Alarm and Sensor Devices
- 3-Axis Design
- Two-Way Audio
- Built-In SD/SDHC/SDXC Card Slot for up to 64GB Local Storage
- Power over Ethernet/DC 12V/AC 24V Support
- Smart IR to adjust the IR LED light across the entire area to get a well illuminated image




ONVIF

Photo Indication & Dimension Diagram



- | | |
|--|--|
| ① LEDs | ⑦ Terminal Block
(For Audio in/out, DIDO) |
| ② RJ45 Connector
(For Ethernet and 802.3 at PoE Plus) | ⑧ TV Out Connector |
| ③ Conduit Plug and Hole | ⑨ Terminal Block (For DC12V / AC24V) |
| ④ Lens | ⑩ Focus Control Bar |
| ⑤ Tilt Screw | ⑪ View Angel Control Bar |
| ⑥ Reset Button/FocusEasy Button | ⑫ SD Card Slot |



Camera

Models	2M, Vari-Focal Lens FocusEasy™
Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR
Image Sensor	Sensor Type : 1/2.8" Sony Exmor Sensor Sensor Resolution : 1920x1080
Minimum Illumination	0 lux (IR ON, B/W) 0.008 lux (IR OFF, B/W) 0.01 lux (F1.4, Color)
IR Illuminators	Built-in IR Illuminators, effective up to 25 meters IR LED: 20pcs IR wavelength: 850nm
Lens	Lens Type: Board Lens Iris: F1.4 Focal Length: f=3mm(W)~10.5mm(T) View Angle (H): 90°~30°/ (V): 49°~17°/ (D):103°~34°
Day & Night ICR	Triggered by Light sensor, Scheduling, Digital Input
Local Storage	Built-in SD/SDHC/SDXC Memory Card Slot Max. 64G

Video

Compression Streaming	H.264 / MPEG4 / MJPEG Simultaneous multiple streams
Video Setting	Multi-Profile Image Management: Day/ Night/ Sunset/ User 1/ User 2 Auto Exposure Control Manual Exposure Control: 1/10000~1/5s Manual Gain Control: 1X ~ 15X Manual White Balance Control: 2000K~7000K
S/N Ratio	>50 dB

Image Resolution	2M (Full HD): 1920x1080 @ 30fps 1M : 1280x720 @ 30fps
-------------------------	--

Events and Alarm Management

Events	Motion Detection/ Schedule/ Audio Detection/ Digital Input/ Temperature Alarm
Alarm	Stream/Snapshot to FTP/Email/Samba/SD-Card/ HTTP/Email Notification/ Digital Output

Audio

Audio Streaming	2-way Audio Support
Audio Compression	G.711, AMR (8 kHz, Mono, PCM)
Audio Input/ Output	Line In/ Out
General	
Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
Power Input/ Operating Temperature	DC12V 1A(1.5A)/ AC 24V/ 802.3af PoE 0°C ~ 50°C (32°F ~122°F)
Max. Power Consumption	DC12V 1A/AC 24V:10.5 Watts 802.3af PoE :12.5 Watts
Environment	Operating Humidity : 10% ~ 80%
Dimension	115.6(D) X 149.95 (H) mm
Weight	509g/1.13lb
Certification	FCC, CE
Viewing System Requirements	OS: Microsoft Windows 7/Vista/XP/2000 Browser: Mozilla Firefox, Internet Explorer 7/8 or above, Safari, Google Chrome Cell Phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.6 or above VLC
Warranty	Limited 2-year warranty

Work Best With

Camera Accessories Options



L-WM-01
Camera Bracket



POE16U *
PoE Injector

Network Equipment Options



PS-588I-v2
8-port 10/100M PoE Fast Ethernet Switch



PS-7242IL-AT
24-port 10/ 100M High Power PoE+ Web Smart Ethernet Switch