

2 Megapixel Mini Dome Network Camera

MD-200Ap

HDTV 1080p/720p • 2M/1.3M Resolution Supported



- Most Intelligent and Professional 2M Outdoor Mini Dome Camera
- HDTV Quality (Full HD 1080p @ 30fps Streaming)
- Wide Camera Angle Adjustment with Pan 35°, Tilt 0-90°, Rotation 180°
- **Intelligent Multi-Profile Sensor Management®** for Different Environments
- Weather-proof (IP67) and Vandal-proof (IK10) with Stylish Design
- Wide Angle of View and Easy to Adjust Focus
- EN50155 Certify with Anti Vibration and Shock
- Built-In Micro SD slot/ TV out Connector Supported
- PoE(802.3af) / M12 Connector / DC12V Supported





ONVIF


Photo Indication & Dimension Diagram



- | | |
|---------------------|--|
| ① Microphone Hole | ⑧ Micro SD/SDHC Card |
| ② Security Screws | ⑨ RJ45 Connector (for Ethernet and PoE:802.3.af) |
| ③ Screw Hole | ⑩ M12 Connector(*) |
| ④ PAL/ NTSC Switch | ⑪ DC12V Connector |
| ⑤ TV out Connector | |
| ⑥ LED Indicators | |
| ⑦ Reset Button Slot | |
- *Cable Connector Variants***



Camera		Audio	
Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR	Audio Streaming	1-way Audio Support
Image Sensor	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution : 1920x1080 pixel	Audio Compression	G.711, AMR (8 kHz, Mono, PCM)
Camera Angle Adjustment	Pan $\pm 35^\circ$ / Tilt 0-90° / Rotation $\pm 180^\circ$	Audio Input/ Output	Built-in MIC
Minimum Illumination	0.6 Lux(B/W) 0.8 Lux (Color)	General	
Local Storage	Built-in Micro SD/SDHC Memory Card Slot	Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
Video		Connectors	Cables with different Options A. RJ45,DC12V B. M12
Compression Streaming	H.264 / MPEG4 / MJPEG Simultaneous multiple streams	Power Input	PoE 802.3af/ M12/ DC12V
Video Setting	Multi-Profile Image Management: Day/ Night/ Sunset/ User 1/ User 2 Auto Exposure/ Gain/ White Balance Control Manual Exposure Control: 1/20000~1/5s Manual Gain Control: 1X ~ 32X Manual White Balance Control:2000K~7000K	Max. Power Consumption	5.5 watts
S/N Ratio	38.1dB	Environment	Operating Temperature -25°C ~ 55°C (-13°F ~131°F), Operating Humidity : 10% ~ 80%
Image Resolution	2M (Full HD): 1920x1080 @ 30fps 1M (HDTV): 1280x720 @ 30fps	Dimension	110(L) X110(W) X 53.7(H) mm
Events and Alarm Management		Weight	460g/1.02lb
Events	Motion Detection Schedule Audio Detection	Housing	Weather-proof (IP67) Vandal-proof (IK10)
Alarm	Stream/Snapshot to FTP/Email/Samba/SD-Card HTTP/Email Notification	Certification	FCC, CE, EN50155, IK10
Product Distinction		Viewing System Requirements	OS: Microsoft Windows 7/Vista/XP/2000 Browser: Mozilla Firefox, Internet Explorer 6/7 or above, Safari, Google Chrome Cell Phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.6 or above VLC
		Warranty	Limited 2-year warranty



Lens Spec					
MD-200Ap	f=4mm	f=6mm	f=8mm	f=2.8mm	f=3.6mm
Lens Type	Board Lens	Board Lens	Board Lens	Board Lens	Board Lens
F Number	F=1.6	F=1.6	F=1.6	F=1.6	F=1.6
FOV(H/V/D)(Normal Mode)	62°/34°/71°	38°/22°/42°	30°/16°/34°	86°/48°/98°	67°/37°/77°
FOV(H/V/D)(Ultra Wide Mode)	86°/46°/80°	45°/30°/50°	39°/21°/46°	114°/66°/130°	90°/47°/103°

Work Best With

Camera Accessories Options



M12 mount Lens



BNCMD-02
TV out Connector Line

Network Equipment Options



PS-588I-v2
8-port 10/100M PoE Fast Ethernet Switch



PS-7242IL-AT
24-port 10/ 100M High Power PoE+ Web
Smart Ethernet Switch